



Marine Product Guide

BILGE PUMPS, WASTE SYSTEMS, WATER PRESSURE SYSTEMS, WASHDOWN PUMPS,
BLOWERS, GENERAL PURPOSE PUMPS



Table of Contents

Bilge Pumping Systems	3
Self-Priming Bilge Pumps	4
Manual Bilge Pumps.....	5
Bilge Pumping Accessories.....	5
Water Pressure Systems.....	6
Stack Pressure Systems	7
Water Pressure System Accessories.....	7
Toilet Systems.....	8
Electric Conversion Kits	8
Electric Toilets	8
Toilet System Accessories.....	9
General Purpose Pumps.....	10
Washdown Pumps & Kits	11
Oil Change Pumps & Systems.....	11
Oil Change Systems	12
Ballast Pumps	13
Circulation Pumps	13
Livewell / Baitwell Pumps & Systems	14
Replacement Impellers	15
Heavy-Duty Radial Blowers, Radial & In-Line Blowers, Inflators.....	15

Bilge Pumping Systems

Rule Standard Bilge Pumps



- Flow rates from 360-4000 GPH (1363-15140 LPH)
- 12, 24 and 32 volt versions available
- Compact, efficient, long-life motors with ability to run dry for short periods
- Back Flow Prevention (360-1100 models only)
- Easy-clean, snap-lock strainer bases
- Stainless steel shafts
- Completely submersible
- Marine-grade blocked wiring
- Rust and corrosion protection
- Built-in Thermal Cut-Off (TCO) provides added protection for pump and vessel
- Silent operation with minimal vibration
- Ignition protection
- CE and ISO 8849 certification

[Complete information on website product page](#)

Rule Bilge Pump Float Switches



- Fits multiple pump sizes
- Removable base for easy cleaning and servicing
- Interchangeable mounting bases for replacement or upgrade (models 35A & 37A)
- Marine-grade blocked wire
- 2-year warranty (Rule-A-Matic and Rule-A-Matic Plus models)
- 5-year warranty (Super Switch model)

[Complete information on website product page](#)

Rule Automatic Bilge Pumps



- Automatic water sensing (no separate float switch required)
- Flow rates from 360-4000 GPH (1363-15140 LPH)
- 12 and 24 volt versions available
- Compact, efficient, long-life motors with ability to run dry for short periods
- Back Flow Prevention (500 -1100 models only)
- Easy-clean, snap-lock strainer bases
- Stainless steel shafts
- Completely submersible
- Marine-grade blocked wiring
- Rust and corrosion protection
- Built-in Thermal Cut-Off (TCO) provides added protection for pump and vessel
- Silent operation with minimal vibration
- Ignition protection
- CE and ISO 8849 certification

[Complete information on website product page](#)

Rule Dry Bilge Pump



- Drains the bilge almost dry, leaving 1/8 inch or less
- Filter-free design
- Self-priming to 9.5 ft. (3 m)
- Able to run dry without damaging the pump
- Up to 4.0 GPM (15 LPM) flow
- Back flow prevention
- Connections for 3/4 inch (19 mm) hose barsbs
- Rotating pump head and ports
- Compact and simple design
- 3/4 inch (19 mm), plastic, 90° thru-hull fitting included

[Complete information on website product page](#)

Rule LoPro bilge pumps



- Choice of operational mode to meet your specific requirements – high or low water sensing mode or automatic timed mode
- Automatic (model no. LP900S) or non-automatic (model no. LP900D) models available
- Max flow rate of 900 GPH (3407 LPH)
- Compact, efficient, long-life motors with ability to run dry for short periods
- Fail safe back up feature
- Fully rotating discharge body to ease install
- Choice of discharge ports supplied with each pump
- Backflow prevention valve
- Horizontal or vertical mounting to accommodate your boat's bilge
- Built-in Thermal Cut-Off (TCO) provides added protection for pump and vessel
- Marine-grade blocked wiring
- Silent operation with minimal vibration
- Ignition protection
- CE and ISO 8849 certification

[Complete information on website product page](#)

Rule-Mate automatic bilge pumps



- Accommodates flow rates of 500 to 2000 GPH (1893 to 7571 LPH)
- Auto Sense Intelligence integral water level sensor controls the pump automatically
- Back- up feature prevents continuous running if sensor is fouled by debris, pump reverts to 2.5 minute cycle mode
- Built-in thermal cut-off (TCO) provides added protection for pump and vessel
- Back flow prevention reduces the amount of water left over in the bilge, reducing odor and helping keep your bilge cleaner (500-1100 GPH models only)
- Hidden air vents in body helps prevent air locking in challenging plumbing installations and helps with the check valve (500-1100 GPH models only)
- Threaded discharge for easier installation

[Complete information on website product page](#)

Self-Priming Bilge Pumps

Jabsco 50880 Series Bilge Pumps



- Flexible installation
- No filter required
- Compact and simple design
- Dry running capability
- Max flow rate of 4.2 GPM (16 LPM)
- Relevant Standards: ISO 8846 MARINE and USCG Regulations for Ignition Protection ISO 8849 MARINE Bilge Pump Standard
- Built to ISO 15083 Specification
- This pump can also be used as a sink and shower drain pump

[Complete information on website product page](#)

23610 Maxi Puppy Bronze DC Pump



- Able to withstand small bilge debris
- Simple design means fewer wearing parts
- ISO 8846 MARINE (ignition protection)
- ISO 8849 MARINE (bilge pump standard)

[Complete information on website product page](#)

Manual Bilge Pumps

Jabsco Amazon Warrior



- Robust, alloy body particularly suited to workboat and safety applications
- Double diaphragm design gives maximum efficiency and added safety, because each side of the pump operates independently
- Solid 18 inch handle assists sustained high outputs of up to 30 GPM (135 LPM)

[Complete information on website product page](#)

Jabsco Amazon Universal



The most versatile manual bilge pump, the Universal can be mounted on or through the bulkhead or deck. Designed for larger and medium sized boats with a flow rate of up to 25 GPM (95 LPM), it's equally good at emptying holding tanks and easily handles solids.

[Complete information on website product page](#)

Jabsco Amazon ThruDeck



- The ultimate compact through deck pump with no less than 16 port variations relative to the body
- Loosening just one screw lets you clear blockages or re-position the body anywhere through 360° relative to the handle position
- Complete with stainless steel handle, mounting clips and provision for safety lanyard
- Sleekly styled through deck kit and cover, with 4 mounting positions relative to the pump

[Complete information on website product page](#)

Jabsco Amazon Bulkhead



- Repositionable ports and body offer an amazing 96 assembly variations
- Complete with stainless steel handle, mounting clips and provision for safety lanyard

[Complete information on website product page](#)

Bilge Pumping Accessories

Jabsco Strainers



- Prevents unnecessary pump breakdowns caused by particles in the water
- Operates in any position
- Corrosion-resistant materials throughout

[Complete information on website product page](#)

Jabsco Non-Return Valves



- Connections for 3/4 inch, 1 inch or 1 1/2 inch (19mm, 25mm or 38mm) ID hose
- 4 1/4 inch long x 2-1/8 inch wide x 2 inch high (10.8cm x 5.5cm x 5cm)
- 0.25lb (0.1kg)
- Simply fit into suction hose
- Corrosion-resistant materials throughout

[Complete information on website product page](#)

MODEL NO.	DESCRIPTION
29295-1011	3/4 inch (19mm) hose
29295-1000	1 inch (25mm) hose
29295-1010	1-1/2 inch (38mm) hose

Rule Panel Switches



These panels control pumps equipped with an automatic float switch or a float switch/pump combo. Models 41 through 45 have three switch positions: automatic, off and manual. Model 49 is a simple, classic-looking on/off switch. Models 41, 42, 45, and 49 are enamel-coated stainless steel. Models 43 and 44 are made from an impact-resistant, UV-stabilized plastic.

MODEL NO.	DESCRIPTION	VOLTS (DC)	MAX AMPS (DC)
41	3-way panel switch - lighted	12	20
42	3-way panel switch - lighted	24-32	10 (24V), 6.5 (32V)
45	3-way panel switch	12-24-32	20 (12V), 10 (24V), 6.5 (32V)
43	3-way rocker panel switch - lighted	12	20
44	3-way rocker panel switch - lighted	24	10
49	2-way panel switch	12-24-32	20 (12V), 10 (24V), 6.5 (32V)

Water Pressure Systems

Jabsco Par-Max Series marine freshwater delivery pumps



- Accommodating flows from 1 GPM (3.8 LPM) to 6 GPM (22.7 LPM)
- Co-molded diaphragm technology ensures long life and durability
- Heavy duty (HD) models feature motors and cast aluminum lower housings for longer life even at high pressures
- Efficient and quiet operation and reduced vibration with dampening mounting feet
- Integrated, sealed pressure switch for on-demand operation
- Versatile installation thanks to its self-priming capability
- Running dry without damage
- Quick-connect ports make for easy installation and servicing
- Reduced cycling and smoother flow thanks to integrated bypass module

[Complete information on website product page](#)

Jabsco Water Pressure Regulators



- Automatically reduces unregulated mains / city water pressure to 45 PSI for worry-free water system performance
- Integral back-flow prevention protects water supply from cross contamination
- Built-in port strainer for easy cleaning
- In-line and permanent flush mount versions available
- In-line version easily connects to garden hose threads
- Flush mount available in white color and optional chrome plate

[Complete information on website product page](#)

Stack Pressure Systems

Jabsco Single and Double Stack Water Systems



Each of these fully assembled, easy-to-install water pressure systems uses either single or double Par-Max 4 pumps, a strainer and a pre-pressurized accumulator tank. That means all the system connection work is done for you in one neat and easily accessible package. The Single Stack provides flow rates up to 4.8 GPM (18 LPM). There are two Double Stack Systems that provide variable flow rates up to 5.8 GPM (22 LPM) or 9 GPM (34 LPM). In heavy-demand situations on larger boats, the twin pump systems provide added security; should one pump fail, the second will continue to operate.

MODEL	MODEL NO.	OUTLETS	VOLTS (DC)	PRESSURE CUTOFF
Single Stack System 4.8	52520-1000	1-4	12	40 psi (2.8 bar)
Double Stack System 5.8	52530-3000	1-5	12	40 psi (2.8 bar)
Double Stack System 5.8	52530-3100	1-5	24	40 psi (2.8 bar)
Double Stack System 9	52530-1000	1-7	12	40 psi (2.8 bar)
Double Stack System 9	52530-1100	1-7	24	40 psi (2.8 bar)

Water Pressure System Accessories

Jabsco Pressurized Accumulator Tanks



Available in 21 ounce (0.5 liter), 1 quart (1 liter) and 2 gallon (8 liter) sizes, each Jabsco Accumulator Tank holds a reservoir of air and water that acts as a cushion, smoothing the water flow and keeping the system quiet. This allows the pump to reduce the on/off cycle, and offers better control of the hot and cold water pressure balance

MODEL NO.	CAPACITY	MAX. PRESSURE
30573-0003	21 oz (0.5L)	125 psi (8.6 bar)
30573-0000	1 qt (1L)	125 psi (8.6 bar)
18810-0000 (US)	1.8 gal (6.8L)	75 psi (5.2 bar)
23240-2000 (EU)	2 gal (8L)	140 psi (10 bar)

Jabsco Strainers



These compact pre-filters prevent particles from jamming valves and causing pump breakdowns. Each one features a screw-off, transparent housing for easy inspection and quick, in-place cleaning.

[Complete information on website product page](#)

Jabsco Aqua Filta (Europe only)



An activated carbon water filter that removes chlorine, unpleasant smells, tastes and colors from marine water systems and uses specially silver-impregnated carbon to inhibit bacterial growth in the filter bed. Aqua Filta absorbs dissolved impurities but retains beneficial mineral salts, thus freshening and cleansing water to make it natural tasting, sweet smelling, and crystal clear.

[Complete information on website product page](#)

Toilet Systems

Jabsco Twist 'n' Lock Manual Toilets



- Powerful self-priming pump for above or below waterline installation
- Reversible mounting allows the pump to be installed on the right or left
- Flexible design suitable for either overboard or holding tank discharge
- Built with corrosion-resistant materials
- Fastenings face front or top for easy access during maintenance
- For use with sea, river, or lake water only
- Complete replacement pump assembly model no. 29040-3000

[Complete information on website product page](#)

Jabsco Lite Flush Electric Toilets



- Space saving stylish design
- Compact size, rotatable seat
- Virtually silent operation
- Choice of leaving bowl wet or dry after use
- Non-clogging large bore flush pump macerates waste
- Uses less than 1.0 amp/hour per day
- Raw water only

[Complete information on website product page](#)

Electric Conversion Kits

Jabsco Manual Toilet to Electric Toilet Conversion Kit



This simple-to-install kit replaces the pump on a Jabsco Twist 'n' Lock manual toilet with an electric pump, using the same hose. It comes ready to fit directly in place of the existing pump. Its spring-return knob has two positions, one for bowl emptying and the other for emptying and flushing.

[Complete information on website product page](#)

Electric Toilets

Jabsco Quiet Flush E2 marine toilet



- Rotatable base and discharge pump for flexibility in tight spaces
- Quick-release system provides easy access to the discharge pump
- Touch sensor panel with three settings, including water-saving, eco flush cycle
- Quiet soft-close seat on regular bowls
- Compact or regular bowl sizes available
- Fresh or raw water rinse models
- Easy-to-clean shroud

[Complete information on website product page](#)

Jabsco Electric marine toilet



- Self-priming rinse pump designed to bring sea, river or lake water into the bowl
- Flexible design suitable for overboard or holding tank discharge
- Built-in backflow preventer guards against flooding and waste return
- Built with corrosion-resistant materials
- Can be mounted 3 ft. (1m) above or below the waterline with appropriate plumbing
- For use with sea, river or lake water only

[Complete information on website product page](#)

Jabsco Deluxe Flush electric marine toilet



- Space saving stylish design
- Household size soft closing seat
- Virtually silent operation
- Fresh or raw water rinse models
- Angle or straight back options available
- Powerful non-clogging large bore flush pump macerates waste

[Complete information on website product page](#)

Toilet System Accessories

Jabsco Macerator Waste Pumps



This waste tank-emptying macerator pump grinds solids into small particles that easily pass through the 1 inch (25mm) discharge port. The Jabsco macerator waste pump is equipped with a protection device that eliminates accidental run dry.

[Complete information on website product page](#)

Jabsco Diaphragm Waste Pump



This super quiet and compact pump has a straight-through waste path that easily passes solids in suspension, making it the ideal solution for emptying holding tanks. Self-priming up to 10 ft. (3m) and capable of extensive dry running, it provides a 5 GPM (19 LPM) output.

[Complete information on website product page](#)

Jabsco Waste Management System



This is an easy-to-install, all-inclusive system consisting of a compact polyethylene holding tank and an integral Run-Dry Macerator Pump. It has a touchpad control panel to monitor waste levels; when required, the user can activate the macerator pump to evacuate waste.

MODEL NO.	VOLTS (DC)
38110-0092	12

Jabsco Toilet Pumpgard



The Pumpgard inlet strainer guards manual or electric toilets from pump malfunctions caused by debris. It has connections for a 3/4 inch (19mm) hose.

[Complete information on website product page](#)

Jabsco Vented Loops



Vented loops guard against the danger of water siphoning over pipework loops in below-the-waterline installations of toilets and bilge pumps. They should be installed in both inlet and outlet pipework.

[Complete information on website product page](#)

Jabsco Y-Valve



This robust valve allows waste to be pumped directly overboard or into a holding tank. Rotating discharge ports simplify installation. Both 1 inch (25mm) and 1 1/2 inch (38mm) inlet ports are included. The Y-Valve can be operated through a bulkhead using the optional shaft extension.

[Complete information on website product page](#)

MODEL NO.	DESCRIPTION
45490-1000	Y-Valve
45500-1000	Extension for through-bulkhead operation

General Purpose Pumps

Rule Slimline Series Submersible Pumps



This family of compact pumps and portable pump kits is designed for a wide variety of uses, both onboard and ashore. Each pump is a combination of a submersible and an in-line pump, and can deliver hot or cold fresh water, seawater, antifreeze and even diesel. Slimline Pumps can be used for deck showers, general washdown, water or diesel transfer, engine winterizing and more.

[Complete information on website product page](#)

Rule Evacuator high volume utility pump



- High capacity, 12V utility pump
- Discharges up to 7700 GPH (29148 LPH)
- Built in back up allows each pump to operate independently, if necessary
- 3-inch barbed discharge port
- Long power lead at 7 ft. (2m)

[Complete information on website product page](#)

Jabsco Water Puppy Commercial Duty



This workhorse is designed for general transfer duty. Self-priming up to 8 ft. (2.4m), it has an output of 540 GPH (2044 LPH).

[Complete information on website product page](#)

MODEL NO.	VOLTS (DC)
18670-0123	12 (not for sale in Europe)
18670-0943	24 (not for sale in Europe)
23680-4003	12 (European model)
23680-4103	24 (European model)

800 GPH Shower Drain Box



- Powerful, high-capacity pump to cope with incoming grey water
- Sealed poly-carbonate lid features tough, impact-resistant material with gasket to prevent water splash
- Fast fix system comprised of lid, pump, filter and float switch can be removed and serviced without tools
- ¾ inch discharge
- Threaded inlet port fittings improves installation by offering several combinations of port fittings including ¾ inch (19mm), 1 inch (25mm), 1-1/8 inch (29mm), straight and 90° elbow fittings
- Easy access side rails plus additional rear bracket option ensure simple installation
- Back flow prevention reduces the amount of water that can siphon back to shower box

[Complete information on website product page](#)

MODEL NO.	DESCRIPTION	VOLTS (DC)
98B	800 GPH (3028 LPH) shower drain system	12
98B-24	800 GPH (3028 LPH) shower drain system	24
99B	1100 GPH (4164 LPH) shower drain system	12
99B-24	1100 GPH (4164 LPH) shower drain system	24

Jabsco Diesel Refueling Pumps

These rugged Jabsco units range in pumping capacity from a reliable 9 GPM (35 LPM) to a mighty 26 GPM (100 LPM). All three are rated for continuous operation and are widely used in the demanding off-road construction sector, so reliability is assured.



MODEL NO.	FLOW RATE GPM (LPM)	VOLTS (DC)
23870-1200	9 (35)	12
23870-1300	9 (35)	24
VR050-1022	13 (50)	12
VR050-1122	13 (50)	24
VR100-1122	26 (100)	24

Washdown Pumps & Kits

Jabsco HotShot Series marine washdown pumps



- 3 GPM (11 LPM) to 6 GPM (23 LPM) and 50 psi (3.4 bar) to 70 psi (4.8 bar) pressure
- Co-molded diaphragm technology ensures long life and durability
- Long life at high pressures with our HD models thanks to their heavy-duty motors and cast aluminum lower housings
- Dampening mounting feet mean efficient and quiet operation with lessened vibration
- Integrated, sealed pressure switch for on-demand operation
- Versatile installation due to self-priming capability
- Able to run dry without damage
- Quick-connect ports make for easy installation and servicing

[Complete information on website product page](#)

Jabsco Quick Connect Deck Nozzles for Washdown Systems



This quick-release, flush-fitting nozzle will quickly connect a Jabsco hose coil and trigger nozzle to the through-deck fitting of a pump and hose installed below decks. Connection and disconnection can be made under pressure, thanks to positive bayonet locks. Quick Connect Deck Nozzles are made of marine-grade stainless steel.

MODEL NO.	DESCRIPTION
31911-0000	Straight quick connector and hose connection ½ inch NPT to ¾ inch garden hose thread (GHT) for US use
31911-0001	Angled quick connector and hose connection ½ inch NPT to ¾ inch garden hose thread (GHT) for US use
31911-0007	Straight quick connector and hose connection ½ inch (13mm) BSP to ¾ inch garden hose thread (GHT) for EU use

Oil Change Pumps & Systems

Jabsco Little Pal and Handy Boy Manual Utility Pumps



These compact brass hand pumps are designed to drain oil from engines and gearboxes. The Little Pal produces up to 1 GPM (4 LPM) output, while the Handy Boy gives up to 1.5 GPM (6 LPM). Both come equipped with hoses, connectors, and dipstick probes for various requirements.

MODEL NO.	HOSE PORT	LENGTH
34060-0010	½ inch hose barb	10.25 inch
34060-0130	GHT inlet x ½ inch hose barb	10.25 inch
33799-0000	½ inch hose barb	12 inch
33760-0000	½ inch hose barb	17 inch
33745-0000	1 inch hose barb	22.5 inch

Jabsco Mini Puppy



Designed for permanent, onboard installation, the Mini Puppy will empty oil sumps into a suitable container. With up to 1.4 GPM (5.3 LPM) output, it's self-priming up to 5 ft. (1.5m), and it's simple to service.

[Complete information on website product page](#)

Jabsco Oil Change Pump



This powerful, stand-alone pump can service a typical V8 engine in just minutes. It's the same high-quality pump used in the Jabsco multi-engine Oil Changer System.

[Complete information on website product page](#)

Jabsco Permanent Mount Oil Changer System



This system consists of a robust, self-priming flexible impeller pump mounted to an easy-to-install base and coupled to a five-port manifold. Factory-fitted with three full-flow ball valves, it allows one system to perform oil changes on two engines and a generator.

[Complete information on website product page](#)

Oil Change Systems

Jabsco Porta-Quick



The ultimate answer to hassle-free oil changing, this robust reversible pump comes ready for use. It's mounted on a 3.5-gallon (13 liter) container and supplied with cables, battery clips and hoses. Operating the Porta-Quick one way empties the oil into the container; flipping the pump switch the other way empties the container into a suitable receptacle. It's self-priming up to 4 ft. (1.2m).

[Complete information on website product page](#)

Jabsco DIY Oil Changer



This simple unit performs quick and easy oil changes for the leisure boat owner.

[Complete information on website product page](#)

Jabsco Flat Tank Oil Changer System



The 3.5 gallon (13 liter) flat tank design of this system makes for a clean and simple oil change on any boat. It allows trouble-free disposal, thanks to the stable, easy-to-carry design.

[Complete information on website product page](#)

Jabsco Drill Pumps



These pumps provide versatile utility. They can transfer fluid almost anywhere that an electric drill with ¼ inch to 3/8 inch chuck can be used.

MODEL NO.	DESCRIPTION
17250-0003	Pump (boxed) with two garden hose thread port adapters

17215-0000	Pump (poly bagged with header card) with garden hose port adapters and ¼ inch x 40 inch probe plus 3 ft. of ½ inch hose for changing oil through a dipstick tube
------------	--

Ballast Pumps

Jabsco Ballast SuperKing



- Includes dry-run impeller
- 25 GPM (94 LPM) flow rate
- Adds approx. 200 lbs. (89kgs) of ballast water per minute
- Reversible pump both fills and empties ballast tanks
- Self-priming to 3 ft. (0.9m)
- Dual impeller design
- Complies with USCG 183.410 and ISO 8846 MARINE (Ignition Protected)

[Complete information on website product page](#)

Jabsco Ballast King



- Includes dry-run impeller
- 15 GPM (57 LPM) flow rate
- Adds approx. 125 lbs. (56kgs) of ballast water per minute
- Reversible pump both fills and empties ballast tanks
- Self-priming to 4 ft. (1.2m)
- Available with or without Reversing Polarity Switch to fill or empty ballast tanks
- Complies with USCG 183.410 and ISO 8846 MARINE (Ignition Protected)

[Complete information on website product page](#)

Jabsco Ballast Puppy



- Adds approx. 80 lbs. (36kgs) of ballast per minute
- Reversible to both fill and empty tanks
- Simple design means fewer wearing parts
- ISO 8846 MARINE (Ignition protection)

[Complete information on website product page](#)

Circulation Pumps

Jabsco Cyclone Centrifugal Pumps



These long-life, continuously rated centrifugal pumps deliver high flows up to 29 GPM (110 LPM) with a maximum pressure of 8.7 psi (0.6 bar).

[Complete information on website product page](#)

Jabsco NEMP Series



The NEMP Series magnetically coupled centrifugal pumps are designed for use with clean fluids, and are ideal for applications requiring safe, leak-free, continuous flow of aggressive chemicals, acids, alkalis, pure and chilled fluids. The models appropriate for this market include the NEMP80/6, NEMP50/7, and NEMP40/4.

[Complete information on website product page](#)

Livewell / Baitwell Pumps & Systems

Rule Tournament Series Livewell Pumps



Keeps tournament-sized catches alive and fresh until returning back to shore.

MODEL NO.	CAPACITY GPH (LPH)	DESCRIPTION
401C	500 (1893)	Through-hull applications requiring an angled pickup tube, 4 inch (100mm) long straight thread
401STC	500 (1893)	Through-hull applications requiring a straight pickup tube, 4-3/4 inch (121mm) long straight thread
401FC	500 (1893)	Seacock-mounted applications requiring a 3/4 inch (19mm) NPT tapered thread
403C	800 (3028)	Through-hull applications requiring an angled pickup tube, 4 inch (100mm) long straight thread
403STC	800 (3028)	Through-hull applications requiring a straight pickup tube, 4-3/4 inch (121mm) long straight thread
403FC	800 (3028)	Seacock-mounted applications requiring a 3/4 inch (19mm) NPT tapered thread
405C	1100 (4164)	Through-hull applications requiring an angled pickup tube, 4 inch (100mm) long straight thread
405STC	1100 (4164)	Through-hull applications requiring a straight pickup tube, 4-3/4 inch (121mm) long straight thread
405FC	1100 (4164)	Seacock-mounted applications requiring a 3/4 inch (19mm) NPT tapered thread

Rule Tournament Series 1600 Livewell Pumps



Designed for the toughest applications, the 1600 GPH (6057 LPH) model is the highest capacity livewell pump on the market. It features a bronze base, an anti-airlock feature and a heavy-duty, long-life motor.

MODEL NO.	VOLTS (DC)
209B	12
209FDP	12, dual port

Rule General Purpose Centrifugal Pumps



Designed for washdown or to circulate water to livewell tanks, the Rule general purpose pump features heavy-duty construction, making it ideal for commercial or pleasure boats. It has a 1-1/2 inch (38mm) inlet and 1-1/2 inch (38mm) discharge outlet with a maximum pumping capacity of 3700 GPH (14006 LPH). It must be mounted below the waterline; although it pumps a lot of water, it operates at low pressure and is not self-priming.

[Complete information on website product page](#)

Rule Replacement Motor Modules



The innovative Tournament Series pumps feature removable motor cartridges, which are fast and convenient to replace.

MODEL NO.	DESCRIPTION
45DR	500 replacement motor cartridge
46DR	800 replacement motor cartridge
47DR	1100 replacement motor cartridge

Jabsco Fish Box Evacuation Pump



This pump easily passes debris such as bait residue, fish scales and ice particles, which are often left in the box after a day of fishing.

[Complete information on website product page](#)

Replacement Impellers

Jabsco Flexible Impellers



We offer replacement impellers for our Jabsco flexible impeller pumps as well as other flexible impeller pump brands.

[See our Impeller Replacement Guide page, including a complete list of available replacement impellers in the Jabsco Impeller Selection Table](#)

Jabsco Flexible Impeller Removal Tools



Using this tool is the easiest way to remove an impeller, especially when the pump is mounted in a cramped space.

[Complete information on website product page](#)

Heavy-Duty Radial Blowers, Radial & In-Line Blowers, Inflators

Rule In-line Blowers



Designed for efficient, high-output operation, these blowers provide ventilation for bilges, engine compartments, galleys and heads. They feature exclusive front and rear shaft seals, corrosion-resistant motors and premium-quality electrical connections for long life.

[Complete information on website product page](#)

Jabsco Heavy Duty Flangemount and Flexmount Blowers



Available in either flange or flexmount form, these powerful blowers are designed for use wherever continuous ventilation is required. A motor life of 5,000 hours is guaranteed for service in the toughest conditions. They provide outputs of 250 cfm (7.1m³/min).

MODEL NO.	DESCRIPTION
35760-0092	12V DC, flangemount
35760-0094	24V DC, flangemount
35770-0092	12V DC, flexmount
35770-0094	24V DC, flexmount

Jabsco Flangemount and Flexmount Blowers



These quiet-running blowers are designed to allow easy connection to ductwork. They incorporate corrosion-resistant materials throughout. Three sizes are available, with outputs of 105 cfm (3m³/min) (12V only), 150 cfm (4.2m³/min) (12 and 24V) and 250 cfm (7.1m³/min) (12 and 24V).

MODEL NO.	TYPE	DESCRIPTION
35115-0010	Flexmount	3m ³ /min output, 12V DC
36740-0000	Flexmount	4.2m ³ /min output, 12V DC
36740-0010	Flexmount	4.2m ³ /min output, 24V DC
35440-0000	Flexmount	7.1m ³ /min output, 12V DC
35440-0010	Flexmount	7.1m ³ /min output, 24V DC
35115-0020	Flangemount	3m ³ /min output, 12V DC

34739-0010	Flangemount	4.2m ³ /min output, 12V DC
34739-0020	Flangemount	4.2m ³ /min output, 24V DC
35400-0000	Flangemount	7.1m ³ /min output, 12V DC
35400-0010	Flangemount	7.1m ³ /min output, 24V DC

Rule High Speed Inflator/Deflator



This super-fast air pump cuts the inflation time for a typical four-man dinghy to less than two minutes. Powered by a standard 12V boat or car battery, it comes with a range of adjustable nozzles to fit plastic, rubber, and sprung valves on all major brands.

[Complete information on website product page](#)